



SPECIFICATIONS		
NUMBER	1	SET.
USE.	DUMBWAITER TABLE TYPE	
CONTROL	AC SINGLE SPEED	
CAPACITY	100	KG.
SPEED	24	M/MIN.
SERVICE FL.	1-3	FLOORS.
TOTAL	3	STOPS.
CAR DOOR	BI PARTING SLIDING DOOR	
LANDING DOOR	BI PARTING SLIDING DOOR	
CAR SIZE	750x750x900	
DIM. IN	MILLIMETERS (mm.)	
GUIDE RAIL CAR	5 K	
GUIDE RAIL CWT	5 K	
ROPES	2xø8mm.	
MAIN SHEAVE	ø320	
DEF SHEAVE	ø240	
MOTOR TYPE	MITSUBISHI	
M/C MODEL NO.	YJF100	
MOTOR POWER	1.5	KW.
ROPING	1:1	
BRACKET	6	SEC.

SPECIAL NOTE (BY OTHERS)

1. VOLTAGE FUNCTION SHALL BE WITHIN A RANGE OF + 5 %--10 %.
2. TEMPERATURE OF MACHINE ROOM SHALL BE BELOW 40° C.
3. THE FOLLOWING CONDITIONS ARE REQUIRED FOR MAINTAINING PERFORMANCE OF THIS ELEVATOR.
 - A. MOISTURE SHOULD BE BELOW 90 % ON MONTHLY AVERAGE AND BELOW 95 % ON DAILY AVERAGE.
 - B. MACHINE ROOM AND ELEVATOR SHAFT SHOULD HAVE NO DUST OR CHEMICAL HARMFUL GAS.
4. WALLS, FLOORS AND CEILINGS OF MACHINE ROOM MUST BE FINISHED BY MOTAR OR OTHERS TO PREVENT THE DUSTS OF CONCRETE.

	POWER FEEDER (BY OTHERS)
--	--------------------------

PLEASE CONSULT THE LIFT CONTRACTOR ABOUT THE DETAILS OF THE POWER SUPPLY TO THE ELEVATOR.

1. POWER FEEDER CAPACITY FROM THE ELECTRIC ROOM TO THE ELEVATOR MACHINE ROOM.
2. TRANSFORMER CAPACITY AND PROTECTIVE DEVICE CAPACITY (ONE-FUSE-BREAKER - OR FUSES) IN THE ELECTRIC ROOM.

POWER SUPPLY (BY OTHERS)

FUSED ISOLATOR TO LOCKABLE IN THE OFF POSITION TO BE PROVIDED FOR EACH LIFT TO SUIT.

LIFT CONTROL

220/380 VOLTS . 50 HERTZ. 4P-1440 RPM
NEUTRAL
EARTH

LIGHTING AND VENTILATION

1. PHASE 220 VOLTS.
15 AMPS LIFT CAR LIGHTING & FAN
15 AMPS SHAFT LIGHTING

REMARKS

 SECTION MARK SHOWS R.C. WALL.

PRICE QUOTATION / AGREEMENT:
SA-D-50-002

PROJECT. NAME.				Dumbwaiter 100 kgs.		REV.	SHEET NO.
LIFT CONTRACTOR.				TYPE.			
DRAWN.		K. Vissanu		CHECKED.		DWF-100-B130	
SCALE.		Non		DATE.		1/2	
				21-06-2024		DWT 012-08	
				DWG.		1 TOTAL 2	

OWNER.
APPROVED.
DATE.